

CFPP124UBL | 24 Port Fiber Optic Patch Panel Unloaded 1U with splice trays



*Images are for representative purposes only

Product Description:

CTS offers rack mount fiber patch panels suitable for terminating single mode or multimode fiber cables with fiber pigtails. The patch panels are designed to accommodate up to 24 fibers with SC connectors or 48 fibers using with LC connectors in 1U rack space.

Standards:

Compliant to ASTM B117-19
RoHS Compliant

Features & Benefits:

19 inch Rack Mountable
Suitable for 24 SC simplex or 48 LC Duplex capacity
Sliding out design
Removable Fiber Optic Splice Trays
Front cable management

Specification:

Material	Cold Rolled Steel 1.2mm thickness
Fiber Connector Insertion Loss	< 0.3dB
Life Span	≥15 years
Voltage Resistance	3000VDC
Insulation Resistance	22 x 10 ⁴ MΩ/500V (DC)
Dimensions	481(W) x 280(D) x 44(H) mm

Packaging Includes:

- ✓ Splice Tray (12Fibers x 2 pcs)
- ✓ Heat shrink tubes
- ✓ 4 Pcs Mounting Screws.
- ✓ Four cable entries on the rear, with 4 pcs cable glands.

Ordering Information:

CFPP124UBL CTS 24 Port Fiber Optic Patch Panel Unloaded type with splice trays Black 1U

Colour Options - Replace (BL) in the part number with GY for Grey Colour, MOQ will be applicable

Version 01-02

