



*Images are for representative purposes only

Technical Specification:

Product Description:

CTS MPO trunk cable is a high-performance pre-terminated optical fiber cable designed for rapid deployment in highdensity environments. It is ideal for use in data centers, enterprise networks, and telecom systems.

Applications:

Datacenters High-speed backbone networks Enterprise networks Cloud computing environments

Standards:


ANSI TIA-568 C3 RoHS Compliant REACH Compliant

Features:

Meets GR or IEC standards Fiber capacity up to 288 Fibers Customizable cable lengths available Factory terminated and tested




Cable Type	Indoor Loose Tube Trunk			
Cable Jacket	Low Smoke Zero Halogen (LSZH)			
Fiber Types	Single Mode		OS2 9/125μm	
	Multi Mode		0M3 / 0M4 / 0M5 50/125µm	
Fiber Count	24, 48, 72, 96, 144, 288			
Connector end A	12-Fiber MPO Male/Female			
Connector end A	12-Fiber MPO Male/Female			
Jacket Colour	OS2	OM3	OM4	OM5
	Yellow	Aqua	Aqua	Lime Green
Insertion Loss	≤ 0.35 dB			
Return Loss	≥ 55 dB (Single Mode)		≥ 20 dB (Multi Mode)	
Operating Temperature	-25 °C to +70 °C			





Method A Connectivity:










Method B Connectivity:










Method C Connectivity:










Part Number Configurator:



Ordering Information:

CFPT924M2FM2FALSYL010	CTS OS2 24 Fiber Trunk Cable 2x12F MPO Female to 2x12F MPO Female Polarity A LSZH Yellow 10m
CFPT348M4FM4FBLSAQ050	CTS OM3 48 Fiber Trunk Cable 4x12F MPO Female to 4x12F MPO Female Polarity B LSZH Aqua 50m
CFPT448M4FM4FBLSAQ100	CTS OM4 48 Fiber Trunk Cable 4x12F MPO Female to 4x12F MPO Female Polarity B LSZH Aqua 100m

For other configuration types, please use the configurator above or Contact CTS Product team

